




# OXBOW B367

A3 Multi Function Printer  
Up to 36 ppm

**oxbow**

# OXBOW B367 Specifications



## Finishing functionalities



# OXBOW B367

## Specifications

A3 multifunctional with 36 ppm b/w.  
Standard ineo print controller with PCL 6 (PCL 5 + XL 3.0), PostScript 3, PDF 1.7, XPS and OOXML support. Paper capacity of 500 + 500 sheets and 100-sheet manual bypass. Media from A6 to A3 and 60 – 220 g/m<sup>2</sup>. 2 GB memory, 250 GB hard disk and Gigabit Ethernet standard.

<b>DF-628 Document feeder</b>	Reversing automatic document feeder, capacity 100 originals
<b>OC-514 Original cover</b>	Cover instead of ADF
<b>PC-113 1 x Universal tray</b>	A5–A3, 500 sheets, 60–220 g/m <sup>2</sup>
<b>PC-213 2 x Universal tray</b>	A5–A3, 2 x 500 sheets, 60–220 g/m <sup>2</sup>
<b>PC-413 Large capacity tray</b>	A4, 2,500 sheets, 60–220 g/m <sup>2</sup>
<b>DK-513 Copier desk</b>	Provides storage space for print media and other materials
<b>MK-602 Attachment kit</b>	For FS-533 installation
<b>FS-533 Inner finisher</b>	50-sheet stapling, 500 sheets max. output
<b>PK-519 Punch kit for FS-533</b>	2/4 hole punching, autoswitching
<b>FS-534 Staple finisher</b>	50-sheet stapling, 3,300 sheets max. output
<b>FS-534SD Booklet finisher</b>	50-sheets staple finisher, 20-sheets booklet finisher, 2,300 sheets max. output
<b>RU-514 Relay unit for FS-534</b>	For FS-534 installation
<b>PK-520 Punch kit for FS-534/SD</b>	2/4 hole punching, autoswitching
<b>JS-506 Job separator</b>	Separation for fax output etc.
<b>KP-101 10-key pad</b>	For use instead of touchscreen

<b>WT-506 Working table</b>	Authentication device placement
<b>FK-513 Fax board</b>	G3 fax, digital fax functionality
<b>KH-102 Keyboard holder</b>	To place USB keyboard
<b>EK-608 USB I/F kit</b>	USB keyboard connection
<b>EK-609 USB I/F kit</b>	USB keyboard connection, Bluetooth (available from Sept. 2015 onwards)
ID card reader	Various ID card technologies
<b>MK-735 Mount kit</b>	Installation kit for ID card reader
<b>AU-102</b>	Finger vein scanner
Biometric authentication	
<b>LK-102v3</b>	PDF/A, PDF encryption, digital signature
PDF enhancements	
<b>LK-105v4</b>	Searchable PDF and PPTX
OCR text recognition	
<b>LK-106 Barcode fonts</b>	Supports native barcode printing
<b>LK-107 Unicode fonts</b>	Supports native Unicode printing
<b>LK-108 OCR A and B fonts</b>	Supports native OCR A and B font printing
<b>LK-110v2 Document converter pack</b>	Generates various file formats incl. DOCX, XLSX and PDF/A
<b>LK-111 ThinPrint® Client</b>	Print data compression for reduced network impact
<b>LK-115v2 TPM activation</b>	Trusted Platform Module for protection of data encryption and decryption
<b>UK-211 Upgrade kit</b>	2 GB memory extension for upgrades
<b>UK-212 Wireless LAN</b>	Wireless LAN and wireless LAN Access Point Mode
<b>SX-BR-4600 Wireless LAN</b>	Wireless LAN to network connector
<b>MK-747 Attachment kit</b>	Installation kit for CU-101
<b>CU-101 Air cleaning unit</b>	Improves indoor air quality by reducing emissions

## Technical specifications

### SYSTEM SPECIFICATIONS

System memory	2,048 MB (standard)
System hard disk	250 GB (standard)
Interface	10-Base-T/100-Base-T/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11b/g/n (optional)
Network protocols	TCP/IP (FTP; SMB; SMTP; WebDAV) (IPv4/IPv6)
Frame types	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
Automatic document feeder	Up to 100 originals; A6–A3; 35–128 g/m <sup>2</sup> RADF optional available
Printable paper size	A5–A3; A6S; thick paper X/Y size input range: width: 90–297 mm; length: 139.7–431.8 mm
Printable paper weight	60–220 g/m <sup>2</sup>
Paper input capacity	Standard: 1,100 sheets Max.: 3,600 sheets
<b>Tray 1</b>	500 sheets; A5–A4; 60–220 g/m <sup>2</sup>
<b>Tray 2</b>	500 sheets; A5–A3; 60–220 g/m <sup>2</sup>
<b>Tray 3 (optional)</b>	500 sheets; A5–A3; 60–220 g/m <sup>2</sup>
<b>Tray 4 (optional)</b>	2 x 500 sheets; A5–A3; 60–220 g/m <sup>2</sup>
Large capacity tray (optional)	2,500 sheets; A4; 60–220 g/m <sup>2</sup>
Manual bypass	100 sheets; A6–A3; custom sizes; 60–220 g/m <sup>2</sup>
Automatic duplexing	A5–A3; 60–209 g/m <sup>2</sup>
Finishing modes (optional)	Offset; group; sort; staple; punch; centre-fold; letter fold; booklet
Output capacity (with finisher)	Max.: 3,300 sheets
Output capacity (without finisher)	Max.: 250 sheets
Stapling	Max.: 50 sheets or 48 sheets + 2 cover sheets (up to 209 g/m <sup>2</sup> )
Stapling output capacity	Max.: 1,000 sheets
Letter fold	Up to 3 sheets
Letter fold capacity	Max.: 30 sheets (tray); unlimited
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 g/m <sup>2</sup> )
Booklet output capacity	Max.: 100 sheets (tray); unlimited
Copy/print volume (monthly)	Rec.: 20,000 pages Max. <sup>(1)</sup> : 48,000 pages

Toner lifetime	23,000 pages
Imaging unit lifetime	110,000 pages/600,000 pages (Drum/Developer)
Power consumption	220–240 V / 50/60 Hz; Less than 1.5 kW (system)
System dimensions (W x D x H)	585 x 660 x 735 mm (Standard configuration of main body)
System weight	Approx. 56.5 kg

### COPIER SPECIFICATIONS

Copying process	Electrostatic laser copy; indirect
Toner system	HD polymerised toner
<b>Copy/print speed A4</b>	Up to 36 ppm
<b>Copy/print speed A3</b>	Up to 18 ppm
<b>Autoduplex speed A4</b>	Up to 36 ppm
<b>1st copy out time</b>	4.3 sec.
Warm-up time	Approx. 20 sec. <sup>(2)</sup>
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1 – 9,999
Original format	A5 – A3
Magnification	25–400% in 0.1% steps; auto-zooming
Copy functions	Chapter; cover and page insertion; proof copy (print and screen); adjustment test print; digital art functions; job setting memory; poster mode; image repeat; overlay (optional); stamping

<sup>1</sup> If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed.

<sup>2</sup> Warm up time may vary depending on the operating environment and usage

**PRINTER SPECIFICATIONS**

Print resolution	1,800 (equivalent) x 600 dpi
Page description language	PCL 6 (PCL 5 + XL 3.0); PostScript 3 (CPSI 3016); XPS
Operating systems	Windows Vista (32/64); Windows 7 (32/64); Windows 8 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008/2008 R2 (32/64); Windows Server 2012/2012 R2 (64); Macintosh OS X 10.x; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Print functions	Direct print of PCL; PS; TIFF; XPS; PDF (v1.7); encrypted PDF files and OOXML (DOCX; XLSX; PPTX); mixmedia and mixplex; "Easy Set" job programming; overlay; watermark; carbon copy print
Mobile Printing	AirPrint (iOS); Mopria (Android); Google Cloud Print (optional); WiFi Direct (optional); ineoPRINT (iOS & Android); NFC Authentication and Pairing (Android)

**SCANNER SPECIFICATIONS**

Scan speed (with optional document feeder)(mono/colour)	Up to 45 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-DPWS; Network TWAIN scan
File formats	TIFF; PDF; Compact PDF; JPEG; XPS; Compact XPS; DOCX; XLSX; searchable PDF; PDF/A; linearised PDF
Scan destinations	2,100 (single + group); LDAP support
Scan functions	Annotation (text/time/date) for PDF; up to 400 job programs; Realtime scan preview

**FAX SPECIFICATION**

Fax standard	G3
Fax transmission	Analogue; i-Fax; Colour i-Fax (RFC3949-C); IP-Fax
Fax resolution	Max.: 600 x 600 dpi (ultra-fine)
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,100 (single + group)
Fax functions	Polling; time shift; PC-Fax; receipt to confidential box; Receipt to e-mail/FTP/SMB; up to 400 job programs

All data relating to the paper capacities of the document feeder, the final processing accessories and the paper cassettes apply to paper weighing 80 g/m<sup>2</sup> unless expressly stated otherwise. All data relating to the speed of printing, scanning or faxing apply to paper of an A4 format weighing 80 g/m<sup>2</sup> unless expressly stated otherwise.

All data relating to paper weights apply to media that are recommended by Konica Minolta. All technical data correspond to knowledge available at the time of going to print. Konica Minolta reserves the right to make technical alterations.

DEVELOP and ineo are registered trademarks/product titles owned by Konica Minolta Business Solutions Europe GmbH.

All other brand or product names are registered trademarks or product titles of their respective manufacturers. Konica Minolta does not accept any liability or guarantee for these products.

**USER BOX SPECIFICATIONS**

Max. storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication); Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling
User box functionality	Reprint; Combination; Download; Sending (e-mail/FTP/SMB and fax); Copy box to box

**SYSTEM FEATURES**

Security	ISO15408/IEEE 2600.2 compliant (in evaluation); IP filtering and port blocking; SSL2; SSL3 and TLS1.0 network communication; IPsec support; IEEE 802.1x support; user authentication; Authentication log; secure print; Hard disk overwrite (8 standard types); Hard disk data encryption (AES 256); Memory data auto deletion; Confidential fax receipt; Print user data encryption
Accounting	Up to 1,000 user accounts; Active Directory support (user name + password + e-mail + smb folder); User function access definition; Biometric authentication (finger vein scanner) optional; ID card authentication (ID card reader) optional
Software	store + find (opt.), convert +share (opt.), Personal Applications (opt.), Enterprise Suite (opt.), Data Administrator (user accounts & cost centres), Card solutions (opt.), Unix/Linux support, SAP support, EveryonePrint (opt.), PCounter (opt.)

