



RICOH IM 2702

A3 Multi Function Printer
Up to 27 ppm

oxbow

RICOH
imagine. change.

RICOH IM 2702

Specifications

MODEL	RICOH IM 2702
GENERAL	
Functions	Print, Scan, Copy, Fax
Operation panel	7-inch Smart Operation Panel
Warm-up time	25 seconds
First output speed	6.5 seconds
Continuous output speed	27ppm
Memory	Standard: 2GB
ARDF capacity	100 sheets
Weight (Mainframe)	46.5kg or less
Dimensions (W x D x H)	587 x 581 x 677 mm
Power source	220 - 240V 50/60Hz
COPIER	
Multiple copying	Up to 999 copies
Resolution	600 x 600 dpi
Zoom	From 25% to 400% in 1% steps
PRINTER	
CPU	ARM CortexA53 800 MHz
Printer language	Standard: PCL5e/6, PostScript3
Print resolution	600 x 600 dpi
Network interface	Standard: Ethernet (1000/100/10BASE), Wireless LAN (IEEE802.11a/b/g/n), USB 2.0-Device (Type-B), USB 2.0-Host
Mobile printing capability	Apple AirPrint [®] , Mopria [™]
Windows [®] environments	Windows [®] 7/8.1/10, Windows [®] Server 2008/2008 R2/2012/2012 R2/2016/2019
Mac OS environments	Mac OS X (V10.11 or Later)
UNIX environments	UNIX Sun [™] Solaris, HP-UX, SCO OpenServer, RedHat [™] Linux, IBM [™] AIX
SAP [®] environments	SAP [®] R/3 [®] , SAP [®] S/4 [®]
SCANNER	
Scanning speed	Mono: 50ipm Color: 50ipm
Resolution	Maximum: 600 dpi
Compression method	MH/MR/MMR, JPEG
File formats	Single Page TIFF, Multi Page TIFF, Single Page JPEG, Single Page PDF, Multi Page PDF, Single Page High-Compression PDF, Multi Page High-Compression PDF
Scan modes	Email, Folder, Network Twain, USB
FACSIMILE	
Circuit	PSTN
Transmission speed	3 seconds
Modem speed	2,400 bps-33.6 Kbps with automatic shift down
Resolution	Standard: 8 x 3.85 line/mm (200 x 100 dpi), 8 x 7.7 line/mm (200 x 200 dpi)
Compression method	MH, MR, MMR
Memory	Standard: 9.7MB
SECURITY	
Features	Locked Print, SSL communication encryption, Transport Layer Security (TLS), SMTP over SSL/TLS, Wireless LAN encryption, Network Protocol, IP filtering
PAPER HANDLING	
Recommended paper size	A3, A4, A5, A6, B4, B5, B6
Paper input capacity	Standard: 500 sheets Maximum: 1,600 sheets
Paper output capacity	Standard: 250 sheets
Paper weight	Tray: 52 - 105g/m ² Bypass: 60 - 216g/m ²
Paper types	Thin Paper, Plain Paper 1, Plain Paper 2, Recycled, Color Paper, Special Paper, Middle Thick Paper, Printed Paper, Preprinted Paper, Prepunched Paper, Letterhead, Bond Paper, Cardstock, Thick Paper 1, Thick Paper 2, Label Paper, OHP, Envelope
ECOLOGY	
Power consumption	Maximum: Less Than 1,550W Ready mode: Less Than 113W Sleep mode: Less than 4W
TEC Value	Less than 1.309 kWh
INPUT TRAY OPTIONS	
1 x 500-sheet paper tray (PB2030)	Paper size: A5-B4, Paper weight: 60-105g/m ²
2 x 500-sheet paper tray (PB2040)	Paper size: A5-B4, Paper weight: 60-105g/m ²
OTHER OPTIONS	
Inner 1 Bin Tray BN2020, Fax Option Type M38, NFC Card Reader Type M38, Bypass Tray Cover Type M16, ADF Handle TypeC, Fax Marker Type 30	

CONTACT OXBOW:



08610 OXBOW



SALES@OXBOWSA.CO.ZA

oxbow