



# OXBOW B950

A3 Multi Function Printer  
Up to 95 ppm

**oxbow**

# OXBOW B950 Specifications



### Intuitive operability

Operate the bizhub like a smartphone or tablet with fully customised user interface



### Security

Secure network integration, data encryption, hard drive overwrite, and advanced user authentication



### Application ecosystem

enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



### Productivity

Reliability, high-speed scanning and printing, combined with powerful finishing functions



### Services efficient

Printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup



### Sustainability

Numerous eco features reduce energy consumption and costs

## 1 ENHANCED FEATURES

- OCR text recognition LK-105v4
- Barcode fonts LK-106
- Unicode fonts LK-107
- OCR A and B fonts LK-108
- Document converter pack LK-110v2
- ThinPrint® client LK-111
- Serverless pull printing LK-114
- Trusted Platform Module LK-115v2
- Antivirus LK-116
- FOIP activation LK-117

## 2 CONNECTIVITY

- Fax board FK-516 x2
- Wireless LAN UK-221
- USB I/F kit EK-610 OR
- USB I/F kit EK-611 OR
- Biometric authentication AU-102 OR
- Card authentication ID card reader OR
- Mount kit MK-735



## 3 OTHERS

- Working table WT-506 OR
- Upright panel WT-519 OR
- 10-Key pad KP-102
- Security kit SC-509
- Replacement SSD EM-908
- Keyboard holder KH-102

## 4 MEDIA INPUT

- Large capacity tray LU303 OR
- Large capacity tray LU205 OR
- Banner tray MK-715

## 5 MEDIA OUTPUT

- Output tray OT-508 OR
- Staple finisher FS-539 OR
- Relay unit RU-515 OR
- Booklet finisher FS-539SD OR
- Relay unit RU-515 OR
- Punch kit for FS-539/SD PK-524
- Staple finisher FS-540 OR
- Relay unit RU-515 OR
- Booklet finisher FS-540SD OR
- Relay unit RU-515 OR
- Punch kit for FS-540/SD PK-526
- Post inserter for FS-540/SD PI507 OR
- Job separator for FS-540 JS-602 OR
- Z-fold unit for FS-540/SD ZU609

### LEGEND

- Mandatory option
- Option
- This option can only be installed with the respective option above it




Corner stapling



Two-point stapling



Two-hole punching




Four-hole punching



Duplex




Combined mixplex/mixmedia



Half-fold



Sheet insertion, report



Letter-fold



Booklet



Offset sorting



Z-fold



Banner printing



Corner Stapling

# OXBOW B950

## Specifications

### ENHANCED FEATURES

LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint® client	Print data compression for reduced network impact
LK-114 Serverless pull printing	Secure and Follow Me printing solution requiring no server application
LK-115v2 Trusted Platform Module	Trusted Platform Module for protection of data encryption and decryption
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all incoming and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit

### CONNECTIVITY

FK-516 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-610 USB I/F kit	USB keyboard connection
EK-611 USB I/F kit	USB keyboard connection; Bluetooth
AU-102 Biometric authentication	Finger vein scanner
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader

### SYSTEM SPECIFICATIONS

System speed A4	Up to 95 ppm
System speed A3	Up to 48 ppm
Autoduplex speed A4	Up to 95 ppm
1st page out time A4	3.2 sec.
Warm-up time	Less than 55 sec.
Imaging technology	Laser
Toner technology	Simitri® V polymerised toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8,192 MB (standard/max)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP(S); Bonjour
Automatic document feeder	Up to 300 originals; A6-A3; 35-210g/m; Dualscan ADF
ADF double feed detection	Standard
Printable paper size	A6-SRA3; customized paper sizes; banner paper max. 1,200 x 297 mm
Printable paper weight	52-300g/m
Paper input capacity	3,650 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1 x 500; A6-A3; custom sizes; 52-256 g/m 1 x 500; A5-SRA3; custom sizes; 52-256g/m 1 x 1,500; A5-A4; 52-256 g/m 1 x 1,000; A5-A4; 52-256 g/m
Large capacity tray (optional)	1 x 3,000; A4; 52-256 g/m 1 x 2,500; A4-SRA3; custom size, 52-256 g/m
Manual bypass	150 sheets; A6-SRA3; custom sizes, banner; 60-300 g/m

### USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication); Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling

### OTHERS

WT-506 Working table	Authentication device placement
WT-519 Upright panel	Working table for upright panel
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 Replacement SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard

### MEDIA INPUT

LU303 Large capacity tray	3,000 sheets,A4,- SRA3 52-256 g/m
LU205 Large capacity tray	2,500 sheets,A4,- SRA3 52-256 g/m
MK-715 Banner tray	Multipage banner feeding

### MEDIA OUTPUT

OT-508 Output tray	Output tray used instead of finisher
FS-539 Staple finisher	50 sheets stapling; 3,200 sheets max. output
FS-539SD Booklet finisher	50 sheets stapling; 20 sheets booklet finisher; 2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/4 hole punching; autoswitching
FS-540 Staple finisher	100 sheets stapling; 3,200 sheets max. output
FS-540SD Booklet finisher	100 sheets stapling; 20 sheets booklet finisher; 2,700 sheets max. output
PK-526 Punch kit for FS-540/SD	2/4 hole punching; autoswitching
RU-515 Relay unit	For FS-539/SD or FS-540/SD installation
PI507 Post inserter for FS-540/SD	Cover insertion; post finishing
JS-602 Job separator for FS-540/SD	Separation of fax output; etc.
ZU609 Z-fold unit for FS-540/SD	Z-fold for A3 prints

### SYSTEM SPECIFICATIONS

Finishing modes (optional)	Offset; Group: Sort; Staple (offline);nPunch; Half-fold; Letter-fold; Booklet; Post insertion; Z-fold
Automatic duplexing	A6-SRA3; 52-256g/m
Output capacity	Up to 200 sheets / up to 3,300 sheets (standard/max)
Stapling	100 sheets or 98 sheets + 2 cover sheets ( up to 300g/m)
Stapling output capacity	Max. 200 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 50 sets; unlimited (without tray)
Booklet	Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300g/m)
Booklet output capacity	Max. 35 booklets; unlimited (without tray)
Power consumption	220-240 V / 50/60 Hz; Less than 2.40 kW
System dimension (W x D x H)	670 x 820 x 1227 mm incl. ADF @
System weight	Approx. 202.0 kg (incl. ADF )

# OXBOW B950

## Specifications

### PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PCL 5e/c; PostScript 3 (CPSI 3016); XPS
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.13 or later; Linux
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS); Mopria (Android); Konica Minolta Print Service (Android); Konica Minolta Mobile Print (iOS/Android) optional: WiFi Direct

### SCANNER SPECIFICATIONS

Scan speed	Up to 140/140 ipm in simplex (mono/colour) Up to 280/280 ipm in duplex (mono/colour)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact XPS; PPTX; PDF/A 1a and 1b optional: Searchable PDF; Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

### COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	Max. A3
Magnification	25-400% in 0.1% steps; Auto-zooming

### FAX SPECIFICATION

Fax standard	Super G3 (optional)
Fax transmission	Analogue; i-Fax; Colour i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

### SYSTEM FEATURES

Security	ISO15408 Common Criteria; IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network communication; IPsec support; IEEE 802.1x support; User authentication; Authentication log; Secure print; Kerberos; Hard drive overwrite; Hard drive data encryption (AES 256); Confidential fax; Print user data encryption optional: Antivirus realtime scanning (Bitdefender®); Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name + password + e-mail + smb folder); User function access definition; Authentication by mobile device (Android) optional: Biometric authentication (finger vein scanner); ID card authentication (ID card reader); Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Box Operator; Web Connection; Print Status Notifier; Driver Packaging Utility; Log Management Utility

<sup>1</sup> Warm-up time may vary depending on the operating environment and usage

<sup>2</sup> If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

– All specifications refer to A4-size paper of 80 g/m<sup>2</sup> quality.

– The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

– The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (6 % coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.

– Some of the product illustrations contain optional accessories.

– Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.

– Konica Minolta does not warrant that any specifications mentioned will be error-free.

– All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

